




PRODUCT INSTALLATION MANUAL

WHEN IT COMES TO HOME, THIS IS THE BEST ANSWER.



www.casainc.com



Call us (9-8 EST): +1 888-257-3857
Email us (24/5): service@casainc.com

Message us: +1 562-551-8092
For sales: dtc@casainc.com



PRODUCT INSTALLATION MANUAL

WHEN IT COMES TO HOME, THIS IS THE BEST ANSWER.



www.casainc.com

TIPS:

- Read the entire instruction manual thoroughly prior to assembly.
- Before installation, verify all received parts are undamaged and complete.
- Ensure required tools (e.g., adjustable wrench, screwdriver) are ready.
- Turn off the main stopcock before beginning installation.
- Thoroughly flush water supply lines and valve block to remove debris.
- Routine cleaning, dampen a soft cloth with clean water to wipe the faucet surface, then dry it with a dry soft cloth.
- NEVER allow steel wool, scouring pads, or chemical cleaners (like dish soap) to contact any faucet surface.

! Retain provided spare O-rings properly for potential maintenance needs later.



Call us (9-8 EST): +1 888-257-3857
Email us (24/5): service@casainc.com

Message us: +1 562-551-8092
For sales: dtc@casainc.com




PRODUCT INSTALLATION MANUAL



1.Position the faucet into the mounting hole.



2.Put rubber gasket, steel washer and the nut in sequence upward. Screw the nut in clockwise and tighten. Then use a screwdriver to fully tighten the locking screw on the nut.



3.Connect the pull down hose and the short hot and cold water supply hoses to the T-connector. Use the provided small wrench to tighten all connections to prevent leaks.



4.Connect the water supply hoses to the angle valves.



5.Clasp the weight to the label "Weight Here".




6.The installation is complete. Turn on the handle to check for any leaks.

Pop-up Drain with Overflow Installation Guide

NOTES:

- Fits for sink WITH overflow hole.
- Clean the sink hole, make sure to remove debris.
- Please avoid using plumber's putty. The seal on top is leak-free. Plumber's putty might cause damage.
- Please avoid using plumber's putty. The seal on top is leak-free. Plumber's putty might cause damage.
- Silicone and plumbing tape can be used for sealing requirement.


① Unscrew components A&B.



② Slide the drain body C through the hole in the sink.



③ Screw components A & B back on as shown.



④ Connect the rear end of the drain to the Drain Pipe.



⑤ Push to activate.

